

Bảng thông số sản phẩm

Thông số kỹ thuật



AvatarOn, 2 switches, 20A, 250V, 2P, LED, White

E8332D20N_WE_G11

Main

Product or component type	Switch
Device application	Control
Load type	Small motor load Serial boost load (SBL) Fluorescent lamps Resistive Incandescent lamp
Colour tint	White

Complementary

Device presentation	Complete product
Rated current	20 A at 250 V AC 50/60 Hz
Switch function	2-pole 1-way
Number of gangs	2 gangs
Number of rocker	2
Clamping connection capacity	3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s) 1 x 6 mm ² for stranded cable(s)
Connections - terminals	Brass terminal
Local signalling	On: LED indicator, LED (amber)
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Flush
Width	86 mm
Height	86 mm
Depth	32 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Operating altitude	2000 m

Relative humidity	0...95 %
Environmental characteristic	UV resistant
Standards	IEC 60669-1 SS 227-1 MS IEC 60669-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	103 g
Package 1 Height	3.2 cm
Package 1 width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.205 kg
Package 2 Height	95 mm
Package 2 width	190 mm
Package 2 Length	195 mm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	7.23 kg
Package 3 Height	21 cm
Package 3 width	30 cm
Package 3 Length	39.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile