


Bảng thông số sản phẩm

Thông số kỹ thuật



Vivace-16A 250V double 8 pin universal socket, White

KB426UES2_WE_G19

Main

Range	Vivace
Product or component type	Socket-outlet
Device presentation	Complete mechanism
Outlet standard	Universal
Colour tint	White

Complementary

Outlet poles configuration	2P + E
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base Polycarbonate: cover Brass: socket terminal Steel: folder terminal PA66: shutter
Device mounting	Flush
Mounting support	Wall mounted
Rated current	16 A at 250 V AC, no inductive load
Network frequency	50 Hz
Connections - terminals	Screw terminals
Clamping connection capacity	130 mm ²
Width	86 mm
Height	86 mm
Depth	27.8 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	120 g
Package 1 Height	3.6 cm
Package 1 width	8.7 cm
Package 1 Length	8.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile